

H290



TECHNICAL DATA

DIMENSIONS [mm]

Width, head open	1900
Width, head closed	1190
Height without rotator and link	1970

WEIGHT [kg]

Without rotator and link, from	1970
--------------------------------------	------

FELLING/CUTTING

SuperCut 100 saw unit, automatic chain tensioning ...	Standard
Maximum cut diameter [mm]	750
Length of saw bar [mm]	900
Chain type404
Chain speed [m/s]	40

FEEDING, TWO-WHEEL DRIVE

with steel feed rollers	1295 / 944-cc: 37.7 / 28.1
Gross feed force [kN]	1404 / 1050-cc: 41.6 / 31.2

Maximum feed speed [m/s]	4.5–6.0
Maximum roller opening [mm]	760

DELIMBING [mm]

Delimiting knives	4 moving, 1 fixed
Delimiting diameter, tip to tip	510
Maximum opening, upper knives	800
Maximum opening, lower knives	870

HYDRAULIC SYSTEM

Maximum operating pressure [MPa]	28
Recommended pump capacity [l/min.]	320–380

CONTROL AND MEASURING SYSTEM	For installation, contact your local Waratah dealer.
------------------------------------	--

OPTIONAL EQUIPMENT

Color marking	Yes
Stump treatment	Yes
Multi-tree-handling (MTH)	No
MenSe feed rollers	Yes
Steel thumbnail feed rollers	Yes
Steel ribbed feed rollers	No
Tireco chain	Yes
Chain and saw-bar kits	Yes
Hydraulic hose kit	Yes
Top saw	Yes

OTHER ACCESSORIES	For more information, please contact your dealer.
-------------------------	---