

# H215E



## TECHNICAL DATA

### DIMENSIONS [mm]

Width, head open .....	1650
Width, head closed .....	1200
Height without rotator and link .....	1900

---

### WEIGHT [kg]

Without rotator and link, from .....	1690
--------------------------------------	------

---

### FELLING/CUTTING

SuperCut 100 saw unit, automatic chain tensioning ...	Standard
Maximum cut diameter [mm] .....	550
Length of saw bar [mm] .....	670
Chain type .....	.404
Chain speed [m/s] .....	40

---

### FEEDING, TWO-WHEEL DRIVE

with steel feed rollers	702-cc: 25
Gross feed force [kN]	

Maximum feed speed [m/s] .....	5.0
Maximum roller opening [mm] .....	550

---

### DELIMBING [mm]

Delimiting knives .....	4 moving, 1 fixed, 2 fixed debarking tools
Delimiting diameter, tip to tip .....	430
Maximum opening, upper knives .....	580
Maximum opening, lower knives .....	610

---

### HYDRAULIC SYSTEM

Maximum operating pressure [MPa] .....	28
Recommended pump capacity [l/min.] .....	260–340

---

**CONTROL AND MEASURING SYSTEM** .....

---

### OPTIONAL EQUIPMENT

Color marking .....	No
Stump treatment .....	No
Multi-tree-handling (MTH) .....	No
MenSe feed rollers .....	No
Steel thumbnail feed rollers .....	No
Steel ribbed feed rollers .....	No
Tireco chain .....	No
Chain and saw-bar kits .....	Yes
Hydraulic hose kit .....	No
Top saw .....	No

---

**OTHER ACCESSORIES** .....

---