

H413



TECHNICAL DATA

DIMENSIONS [mm]

Width, head open	1450
Width, head closed	1140
Height without rotator and link	1330

WEIGHT [kg]

Without rotator and link, from	940
--------------------------------------	-----

FELLING/CUTTING

SuperCut 100 saw unit, automatic chain tensioning	Standard
Maximum cut diameter [mm]	580
Length of saw bar [mm]	640/750
Chain type404
Chain speed [m/s]	40

FEEDING, FOUR-WHEEL-DRIVE with steel feed rollers

Gross feed force [kN]	400 / 250-cc: 19
	500 / 315-cc: 23
Maximum feed speed [m/s]	4.8–5.6
Maximum roller opening [mm]	560

DELIMBING [mm]

Delimiting knives	4 moving, 2 fixed
Delimiting diameter tip to tip	420
Maximum opening upper knives	560
Maximum opening lower knives	570

HYDRAULIC SYSTEM

Maximum operating pressure [MPa]	28
Recommended pump capacity [l/min.]	240–280

CONTROL AND MEASURING SYSTEM

For adaptation, contact your local Waratah dealer.

OPTIONAL EQUIPMENT

Color marking	Yes
Stump treatment	Yes
Multi-tree-handling (MTH)	Yes
MenSe feed rollers	Yes
Moipu feed rollers	Yes
Steel thumbnail feed rollers	Yes
Steel V-profile feed rollers	Yes
Steel ribbed feed rollers	Yes
Chain and saw bar kits	Yes
Hydraulic hose kit	Yes
Top saw	No

OTHER ACCESSORIES

For more information, please contact your dealer.